



Fiord

Design: Louise Sigvardt & Tone Barnung

Type: Upholstery

Composition: 92% new wool, 8% nylon

Yarn type: Worsted

Binding: Dobby

Width: Approximately 55 inches (140 cm)

Weight: Approximately 500 g/lin.m

Repeat: None

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week.
Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary.

More info: Maintenance instruction – please see website,
kvadrat.dk/care-and-maintenance



10 year
warranty



Fiord

Abrasion

Approx. 60.000 Martindale rubs, EN ISO 12947

Pilling

Note 4-5, EN ISO 12945

Seam slippage

Warp: 4.5 mm Weft: 5.0 mm

Lightfastness

Note 5-7 ISO 105-B02

Fastness to rubbing

Dry note 3-5 ISO 105-X12

Wet note 3-5 ISO 105-X12

Flame resistance

AS/NZS 3837 class 2

BS 5852 Crib 5 with treatment *

BS 5852 Part 1

DIN 4102 B2

EN 1021-1/2

GB 50222 B1 with treatment *

IMO FTP Code 2010:Part 8

NF D 60 013

NFPA 260

SN 198 898 5.3 with treatment *

UNI 9175 1IM

US Cal. Bull. 117-2013

** To pass this test flame retardant treatment is necessary.*

We are looking into more environmental friendly alternatives but for now the external finisher may use a treatment containing halogen based flame retardants

Benefits of wool

Wool is a renewable resource

Wool is very comfortable because of its ability to absorb/give off humidity

Wool is flame retardant

Wool is biodegradable

Wool is naturally soil resistant

Wool ages with grace

Quality benefits

Complies with Möbelfakta

Very good abrasion

Very good lightfastness

Flame retardant

Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye
and heavy metal restrictions
Complies with REACH regulation
Environmental Product Declaration (EPD)
Health Product Declaration (HPD)

Reduced emissions

Greenguard and Greenguard Gold certified
greenguard.org

Warranty

10 years. See terms and conditions on kvadrat.dk

For further information
kvadrat.dk